

ARIGATO CORPORATION

〒339-0076 368 Heirinji, Iwatsuki, Saitama

City, Saitama

Email: sales@arigatocorp.jp

Tel : +8148-797-8020 | FAX: +81 48-797-9410

Website: https://www.arigatocorp.jp



KATO		
MACHINE NAME:		KRM-13H-III
Maximum Lifting Capacity		5.3 m / A: 13,000 kg x 1.7 m (1 ROW) 9.04 m / A: 10,000 kg x 4.9 m (2 ROW) 15.27 m / A: 6,500 kg x 4.5 m (3 ROW) 16.52 m / A: 5,000 kg x 4.5 m (4 ROW) 20.62 m / A: 3,700 kg x 4.5 m (5 ROW) 24.0 m / A: 3,200 kg x 4.5 m (6 ROW) 3.5 m: 1,600 kg x 7.5 m (8 ROW)
Boom Length	Maximum Boom Length m	24
	Number of Boom Steps	6
JIB SPECS	Jib Length m	9.3
	Total Length of Boom and Jib m	33.3
Outrigger Spread	Maximum Boom Length	4.8
	Medium "	4.3
	Low "	2.7
Safety Device		"ACS" (Automatic Crane Stop)
		Load moment indicator Boom angle indicator"
Carrier Specifications	Maximum Speed	km/h 49.0
	Engine Type	4M50-TLE3A
	Maximum output	129 kW / 2,700
	Gross Weight	t 13.8
	Steering	Hydraulic Power Steering
	Brake	Service: Air-Over-Hydraulic Brakes Parking: Spring-Applied Brakes
	Tires	Front: 275 / 80 R22.5 (14J)
		Rear: 275 / 80 R22.5 (14J)
Dimensions/Weight	Overall Length	mm 7,440.0
	Overall Width	mm 2,495.0
	Overall Height	mm 3,385.0
	Wheelbase	mm 2,760.0
	Minimum Ground Height	mm 280.0
	Vehicle weight	kg 13,810.0

*Performance and numbers may differ from specifications herein.

*This information is not promised or guaranteed to be correct, current, or complete, and this may contain technical inaccuracies or typographical errors